

Technical Data Sheet

HPMC E50 FG

1 <u>Description</u>

HPMC E50 FG is low viscosity Hydroxypropyl Methyl Cellulose (HPMC) which is designed for using in a wide range of food ingredient additives applications.

2 Physical Analysis

Appearance	:	White to slightly off-white fibrous or granular powder.
Identification A to E	:	Conform
Solution appearance	:	Conform
Methoxy	:	28.0-30.0%
Hydroxypropoxy	:	7.0-12.0%
Loss on drying	:	5.0% Max
Residue on ignition	:	1.5% Max
рН	:	5.0-8.0
Apparent viscosity	:	40.0-60.0cps
Particle size	:	Min. 98% pass through 100 mesh
Heavy Metals		
Heavy Metal	:	≤10ppm
Arsenic	:	≪3ppm
Lead	:	≪3ppm
Mercury	:	≤1ppm
Cadmium	:	≤1ppm
<u>Micro bacteria</u>		
Total plate count	:	≤1000cfu/g
Yeast and Mould	:	≤100cfu/g
Coli form	:	Absent/g
Salmonella	:	Absent/g
Packaging		

5 <u>Packaging</u>

3

4

25kg fibre drum with inner liner.

6 <u>Regulation</u>

Meets all requirements of FCC,FSSC,E464 Hydroxypropyl Methyl Cellulose.

The information supplied is presented in good faith and has been derived from sources believed to be reliable. Since conditions of use are beyond our control, all risks are assumed by the user. No representation is expressed or implied, and nothing herein shall be construed as permission or recommendation to practice a patented invention without license.